



€ 30.222 VAT excluded

L 35		L35 F	L 35 H	L 35 K	L 35 L
Wheelbase	X	2750	3350	3845 ⁽⁵⁾	4175 ⁽⁵⁾
Overall length	K	5295	6015	7032	7565
Body length min. ⁽¹⁾	W	3535	4255	5272	5805
Body length Max. ⁽¹⁾	W	3820	4490	5502	6030
Rear overhang	Y	1435	1555	2077	2280
Chassis height	T	730		720	
Overall height	H	2150		2160	
Rear axle width	L			1865	
Cab width ⁽²⁾	L1			1815	
Body width ⁽³⁾	C			2120	
Front axle to back of cab	D min			650	
Front overhang	A			1110	
Frame internal size	I			700	
Front track	C1			1475	
Rear track	C2			1425	
Minimum Road Clearance	-			190	
Turning diameter (m) ⁽⁴⁾	-	11,3	13,5	15,2	16,4
WEIGHT (kg)					
Unladen weight ⁽⁶⁾		2240	2300	2350	2400
Unladen weight front axle		1580/660	1600/700	1625/725	1650/750
Minimum weight vehicle equipped				2585	
Gross Vehicle Weight (GVW)				3500	
Front/rear total weight				2100 / 2435	
Max trailer weight unbraked/Max trailer weight braked				750 / 3500	

- The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
- Excluding turn signal and side mirrors
- Possible widths with optional mirror brackets 1865/1945 – 1945/2120 – 2120/2275
- Curb to curb turning diameter
- Wheelbase modified (see thw optional equipment)
- The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES + 35 Kg (25/10)

L 35 - Wheelbase (mm) F 2750 - H 3350 - K 3845 - L 4175

FEBRUARY 2021

€ 30.222 (**)

Equipment	NEES 2 (only Wheelbase F)	€ 1290 (**)
	Right-hand drive (*)	€ 1182 (**)
(*) only Wheelbase F e NEES 2; (*) according to availability		(**) VAT excluded
Standard features		
<ul style="list-style-type: none"> • EGR - DPD - SCR • MID display • Engine exhaust brake • Reverse warning buzzer • Immobilizer 	<ul style="list-style-type: none"> • Central locking with remote control • Suspended seat • Power operated windows • Day-time running lights 	<ul style="list-style-type: none"> • Fog lamps Fr and Rr • Radio DAB+ with USB • Head lamps control levelling • Steering adjustable (tilting and height)
Optional	. Air conditioning	€ 1089 (**)
	. Wheelbase modified	Ask to your dealer
	. Body builder Controller	€ 354 (**)
Engine	ISUZU 4JJ1E6N Diesel Engine 4 cylinders. Intercooler, common-rail with direct injection Variable-geometry turbocharger DISPLACEMENT 2999 cm ³ POWER 110kW (150 hp) 2800 rpm TORQUE 375 Nm 1600 – 2800 rpm EMISSIONS REGULATIONS EURO VI OBD-D.	
Safety systems	ABS with BAS (Brake Assist System) ESC (Electronic Stability Control) with ASR SRS Driver Airbag	
Tank	68 L Wheelbase F – 93 L Wheelbase H-K-L	16 L Ad-Blue®
Gearbox and Final drive ratio	5 gear MYY5A – 5.315 - 2.908 - 1.558 - 1.000 - 0.721; Reverse 5.068; Final gear ratio 3.909 (43/11)	
Transmission control	Manual	NEES 2
Dimensions of the chassis	Width 65 mm, Height 180 mm, Thickness 4 mm	
Number of seats	3	
Axle	2 the rear one with twin wheels.	
Tires	Front 205/75 R16C simple. Rear 205/75 R16C dual.	
Brakes	Front and rear: ventilated discs with asbestos-free linings. Hydraulic system, with vacuum brake booster EEC standards with ABS, independent circuits on both axles. Drum parking brake on the transmission shaft.	
Suspensions	Front and rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.	
Electric system	Nominal voltage 24V - Generator 90A - 2 x Battery 70Ah	