



190 hp Série Bleu OBD-E (*9,5 ton*)





|--|

Q 95		Q 95 H	Q 95 K	Q 95 M
Wheelbase	F	3365	3815	4475
Overall length	OAL	6223	6873	8053
Body lenght min. (1)	W	4355	5005	6185
Body lenght Max. (1)	W	4655	5305	6485
Rear overhang	ROH	1730	1930	2450
Chassis height	EH	•	830	
Overall height	ОН		2275	
Rear axle width	BW	2129		
Cab width ⁽²⁾	OW	2040		
Body width ⁽³⁾	6,1	2345		
Front axle to back of cab	D min	740 (6)		
Front overhang	FOH	1128		
Frame internal size	LaC	850		
Front track	AW	1746		
Rear track	CW	1650		
Minimum Road Clearance	HH		195	
Turning diameter (m) (4)	Dia	13,8	15,3	17,5
	WEIGHT	(kg)		
Unladen weight ⁽⁵⁾		3365	3405	3445
Unladen weight front axle		2160/1205	2200/1205	2220/1225
Gross Vehicle Weight (GVW)		9500		
Front/rear total weight		3400 / 6800		
Max trailer weight unbraked/ Max trailer weight braked		750 / 3500		

- The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
- Excluding turn signal and side mirrors
 Possible widths with optional mirror brackets 2129/2170 2170/2345 2345/2465
- Curb to curb turning diameter
 The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES + 35 Kg 25/10).
- With minimum counterframe height = 100 mm

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.

$Q\ 95$ - Wheelbase (mm) H 3365 - K 3815 - M 4475

JUNE 2023

	· · · · · · · · · · · · · · · · · · ·			
Equipment	NEES 2 + Cruise control			
Standard features				
• EGR - DPD - SCR • MID display • Engine exhaust brake • Side mirrors heated and electric • Immobilizer • Seat belt buzzer • Central locking with remote control	 Suspended seat Cab overturning safety Steering adjustable (tilting and height) Fog lamps Fr and Rr Radio DAB+, USB, Bluetooth Reverse warning buzzer Air conditioning 	 Head lamps control levelling Front led lights Day-time running lights Automatic headlight lighting Speed limiter (90km/h) Power operated windows 		
Optional				
Engine	ISUZU 4HK1E6C Intercooler, common-rail with direct injection Variable-geometry turbocharger DISPLACEMENT 5193 cm³ POWER 140kW (190 hp) 2600 rpm TORQUE 510 Nm 1600 - 2800 rpm EMISSIONS REGULATIONS EURO VI OBD-E.			
Safety systems	ABS ESC (Electronic Stability Control) w LDWS AEBS SRS 2 Airbag (Driver/Pass.)	ith ASR		
Tank	90 L	16 L Ad-Blue [®]		
Gearbox and Final drive ratio	6 gear MZZ6F 6.369 - 3.767 - 1.966 - 1.355 - 1.000 - 0.782; Reverse 6.369; Final gear ratio 4.777 (43/9)			
Transmission control	Manual	NEES 2		
Dimensions of the chassis	Width 70 mm, Height 216 mm, Thickness 6 mm			
Number of seats	3			
Axle	2 the rear one with twin wheels.			
Tires	Front 225/75 R17,5C simple. Rear 225/75 R17,5C dual.			
Brakes	Front and rear: ventilated discs with asbestos-free linings. Follow CEE regulation with ABS 4 channels. Brake type: Full Air dual circuit and engine exhaust brake. Pneumatic parking brake on rear axle.			
Suspensions	Front and rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers. Front and Rear Stabilizer bar.			
Electric system	Nominal voltage 24V - Generator 80A - 2 x Battery 90Ah			